



One audio satellite receiver...



(Deliver Rap, Rhapsody, and Rock all at the same time)
...doing the work of three.





Open Your Home to the Power of Satellite Radio

TriplePlay XM-3000—Multiplying the Power of XM Satellite Radio

Now you can enjoy all the advantages of XM Satellite Radio throughout your home with the *Antex TriplePlay XM-3000*. Designed to integrate into any multi-room entertainment system, the XM-3000 lets you stream three XM radio stations simultaneously to any room in your house.

TriplePlay installs quickly and easily. And once installed, you'll have immediate access throughout the home to more than 100 channels of the most dynamic programming available anywhere.

Customize Your Listening Tastes

TriplePlay let's you select from XM's 68 Commercial-Free Music Channels, 33 Channels of News, Sports, Talk & Entertainment, 21 dedicated Channels of XM Instant Traffic & Weather, and the deepest playlist in the industry with access to over two million titles! Hear today's hits to R&B oldies to classical masterpieces, from authentic country and real bluegrass to cool jazz, hot Latin, reg-

gae, rock, dance, new age and even kid's music.

What's more, *TriplePlay* gives you the option to select the programming for three independent listening zones from the front panel of the receiver, while also giving you independent control remotely from within each zone. With *TriplePlay*, a family can be listening to the latest top 10 in your living room, sports in the family room and the latest breaking news around the world in your bedroom.

Beyond AM. Beyond FM. XM.

- The #1 satellite radio service
- · Over 120 digital channels
- The most 100% commercial-free music
- In-depth, 24/7 traffic and weather in the top 21 markets
- The most live music and deepest playlists
- Comprehensive news and sports coverage
- The best sound quality in satellite radio
- Only XM offers: MTV, VH1, NASCAR Radio, CNN, MSNBC and FOX Sports Radio

TriplePlay Feature Highlights

Front Control Panel—Locally control *TriplePlay's* receiver and view the status of each zone instantly.

Multizone Display—A wealth of information from *TriplePlay*'s single display front panel, including instant status of the receiver in the setup, category list, parental lock and normal modes of operation, and full title, track, and artist information for all three zones.

Flexible Control Options—Use the front panel, an external controller unit via the RS232 control port, a hardwired IR port, or an IR remote control unit to control *TriplePlay's* receiver.

Multiple Zone Presets—Store 10 presets for each of *TriplePlay's* three zones. That's 30 presents in all.

Analog and Digital Outputs—Past, present and future compatibility is guaranteed with *TriplePlay's* analog and digital outputs. The receiver uses the latest TOSLink Digital S/PDIF Output and more traditional RCA Stereo Outputs for each zone.

Stream Lock Parental Control—*TriplePlay* is a parent's dream, offering you the ability to block channels you don't want your family to hear. If you forget the parental control code, use the master password reset function to re-gain channel access.

Channel Skip Control—Want TriplePlay to play only the channels you like best and skip others? This feature allows you to designate the channels you want to hear, and exclude those you don't, all the while retaining the ability to scan through all channels using regular channel commands.

Antenna—*TriplePlay's* easily installable, high gain omnidirectional antenna is small in size and big in performance.

TriplePlay XM-3000 System

The product as packaged for sale includes the following:

- Antex branded XM Satellite Radio Multizone Receiver
- · Remote Control
- · Antenna with integrated 30' cable
- 3 RCA stereo audio patch cables
- User Manual

Front Panel

- Main Display 160x240 graphical LCD, backlit with display indication for all 3 zones
- Power On/Off button
- · Category and zone select buttons
- Channel preset and direct entry buttons
- · Infrared receiver eye

General Specifications

- Unit Size 17.75" W x 3.5" H x 12"D
- LNA Supply: 4.5 volts, 200mA
- Power Input: 85–140VAC, 50–60Hz
- · Certifications: UL, FCC Part 15 Class B
- Operating Environment: 0–40C, 0-95% Relative Humidity non-condensing

System RF Specifications

- Physical: Single SMA to Antenna
- Input Frequency: 2.33-2.35GHz
- Input Level: -85dBm to -5dBm
- Input Impedance: 50 ohms
- Demod / Descrambling: XM Proprietary



1125 West 190th Street, Suite 100 Gardena, California 90248 Ph. 310-532-3092 Fax: 310-532-8509

Analog Performance

- · Compression: AAC Plus
- Conversion: 24 bit D/A
- Frequency Response: 20 to 20kHz ±3dB
- Harmonic Distortion: < 0.02%
- Output Level: 2VRMS maximum

Rear Connectors

- RF Input: Female SMA
- Audio Line Out Connectors: 3 pairs RCA: Left, Right
- Digital Audio: 3X S/PDIF TOSLink
- IR: Hard wired IR input via a 3.5mm tip jack connector
- Data Control Port: DB9 RS232: data rate: 19,200 baud, no parity, 8 data bits, 1 stop bit, 3 wire (Rx, Tx & Gnd) interface
- · AC input: 3 wire cord

Copyright © 2004 Antex Electronics Features and specifications subject to change without notice. Trademarks and logos are properties of their respective companies.

